




CARBON DIOXIDE



Carbon Dioxide is the trusted non-conductive clean agent and is most effective for dealing with electronic equipment fires. CO2 is suitable for use on Class B and Class C fires.

TYPICAL USES: For protecting sensitive electronic equipment in offices, classrooms, churches, parking garages, and hotel/motel assembly halls and guest areas. For protecting sensitive electronic equipment in businesses such as retail stores, light manufacturing facilities, research facilities, auto dealerships, vehicle/aircraft/marine service centers, and manufacturing processes such as painting, dipping, and coating.

Not UL Listed or suitable for use on fires involving cooking oil and grease. Recommended for use on sensitive electronic equipment.



Model	5CD	10CD	15CD	20CD
PL. #	45100	45600	46100	46600
AGENT CAPACITY	5 lb. (2.27 kg)	10 lb. (4.54 kg)	15 lb. (6.8 kg)	20 lb. (9.07 kg)
UL RATING	5-B:C	10-B:C	10-B:C	10-B:C
DISCHARGE TIME	8 sec	10 sec	15 sec	20 sec
RANGE (FT/M)	4-8 / 1.2-2.4	4-8 / 1.2-2.4	4-8 / 1.2-2.4	4-8 / 1.2-2.4
BRACKET	Wall	Wall	Wall	Wall
USCG APPROVAL	Type B:C Size I	Type B:C Size I	Type B:C Size II	Type B:C Size II
SHIP WEIGHT	13.75 lb. (6.3 kg)	27.75 lb. (12.6 kg)	37.75 lb. (17.1 kg)	49 lb. (22.2 kg)
UNIT HEIGHT	17.375 in (44.1 cm)	19.75 in (50.2 cm)	26.375 in (67 cm)	26.875 in (68.2 cm)
UNIT WIDTH	8.25 in (21 cm)	12 in (30.5 cm)	12 in (30.5 cm)	13 in (33 cm)
UNIT DIAMETER	5.25 in (13.3 cm)	6.89 in (17.5 cm)	6.89 in (17.5 cm)	8 in (20.3 cm)



FOR MORE INFORMATION CALL 1-888-926-1365
 Superior Specialty Supply • 9 Council Drive • PO Box 417 • Woodsboro, MD 21798 • www.sssupply.com