

**STANDARD DRY CHEMICAL**



Standard (BC) Dry Chemical is a sodium bicarbonate based extinguishing agent that is suitable for use on Class B and Class C fires.

**TYPICAL USES:** For flammable liquid hazards in public areas such as offices, classrooms, churches, parking garages, and hotel/motel assembly halls and guest areas. For flammable liquid hazards in businesses such as retail stores, light manufacturing facilities, research facilities, auto dealerships, vehicle/aircraft/marine service centers, and manufacturing processes such as painting, dipping, and coating.

Not UL Listed or suitable for use on fires involving cooking oil and grease. Not recommended for use on sensitive electronic equipment.



LISTED



USCG  
Approved



DOT  
Compliant

Model	2.5 STD V/B	5.5 STD	5.5 STD V/B	10 STD	20S STD
Pt. # ALUM. VALVE	13415	11014	13514	11840	12220
AGENT CAPACITY	2.5 lb. (1.13 kg)	5.5 lb. (2.5 kg)	5.5 lb. (2.5 kg)	10 lb. (4.54 kg)	20 lb. (9.07 kg)
UL RATING	10-B:C	40-B:C	40-B:C	40-B:C	120-B:C
DISCHARGE TIME	9 sec	14 sec	14 sec	14 sec	20 sec
RANGE (FT/M)	9-15 / 2.7-4.6	12-18 / 3.7-5.5	12-18 / 3.7-5.5	15-21 / 4.6-6.4	15-21 / 4.6-6.4
OPERATING PRESSURE	100 psi (689 kPa)	195 psi (1344 kPa)	195 psi (1344 kPa)	195 psi (1344 kPa)	195 psi (1344 kPa)
BRACKET	Vehicle	Wall	Vehicle	Wall	Wall
USCG APPROVAL	Type B:C Size I	Type B:C Size I	Type B:C Size I	Type B:C Size II	Type B:C Size III
SHIP WEIGHT	5.5 lb. (2.5 kg)	10.5 lb. (4.8 kg)	10.75 lb. (4.9 kg)	18.25 lb. (8.3 kg)	33.5 lb. (15.2 kg)
UNIT HEIGHT	14.75 in (37.5 cm)	16.375 in (41.6 cm)	16.375 in (41.6 cm)	21 in (53.3 cm)	21.25 in (53.8 cm)
UNIT WIDTH	4.875 in (12.4 cm)	7.25 in (18.4 cm)	7.25 in (18.4 cm)	7.75 in (19.7 cm)	8.75 in (22.2 cm)
UNIT DIAMETER	3.375 in (8.6 cm)	4.25 in (10.8 cm)	4.25 in (10.8 cm)	5.125 in (13 cm)	7.5 in (19.1 cm)



**FOR MORE INFORMATION CALL 1-888-926-1365**  
 Superior Specialty Supply • 9 Council Drive • PO Box 417 • Woodsboro, MD 21798 • [www.sssupply.com](http://www.sssupply.com)