



**CARBON DIOXIDE**



Meets or exceeds:  
ANSI/UL 154 & 711  
English / Spanish labels



Meets or exceeds:  
CAN/ULC-S503 & S508  
English / French labels

## Built tough and easy to service

STRIKE FIRST Carbon Dioxide fire extinguishers are designed for:



**CLASS B**  
flammable liquids & gases



**CLASS C**  
electrical conductivity

- Well suited for corrosive environments
- Super durable polyester powder paint finish with superior corrosion resistance
- Industrial strength aluminum cylinder
- Stainless steel handles, pull pin, retaining chain and hose band
- Chrome-plated solid brass valve
- Strong impact-resistant horn
- Colour and bar-coded labels for accurate service

[www.strike-first.com](http://www.strike-first.com)



**FOR MORE INFORMATION CALL 1-888-926-1365**  
Superior Specialty Supply • 9 Council Drive • PO Box 417 • Woodsboro, MD 21798 • [www.sssupply.com](http://www.sssupply.com)

Complies with NFPA 10 Standard

D.O.T. Approved Cylinder

U.S.C.G. approved with bracket listed on label

Temperature range: -22°F to 120°F (-30°C to 49°C)

5 Year Warranty



CAPACITY	5 lb	10 lb	15 lb	20 lb
UL Model No.	SF-5C02A	SF-10C02A	SF-15C02	SF-20C02
ULC Model No.	WBSF-5C02	WBSF-10C02	WBSF-15C02	WBSF-20C02
UL Rating	5-B:C	10-B:C	10-B:C	10-B:C
ULC Rating	5-B:C	10-B:C	10-B:C	10-B:C
U.S.C.G. Approval	Type B:C Size I	Type B:C Size II	Type B:C Size II	—
Range	6 - 12 ft (2 - 2.5 m)	6 - 12 ft (2 - 2.5 m)	6 - 12 ft (2 - 2.5 m)	6 - 12 ft (2 - 2.5 m)
Discharge Time	10 sec	10 sec	15 sec	20 sec
Height	17 1/4" (44 cm)	19 3/4" (50.2 cm)	26 1/4" (66.7 cm)	26 1/4" (66.7 cm)
Width	8 1/2" (21.6 cm)	11 3/4" (30 cm)	11 3/4" (30 cm)	12" (30.5 cm)
Diameter	5 1/4" (13.3 cm)	7" (17.8 cm)	7" (17.8 cm)	8" (21 cm)
Weight	13 1/2 lb (6.12 kg)	28 lb (12.7 kg)	37 lb (12.3 kg)	48 1/8 lb (21.8 kg)
Standard Bracket	Wall	Wall	Wall	Wall
Optional Brackets	HDVB-2	HDVB-3	HDVB-3	—



**STRIKE FIRST**  
CORPORATION

777 Tapscott Road  
Scarborough  
Ontario, Canada M1X 1A2



**FOR MORE INFORMATION CALL 1-888-926-1365**  
Superior Specialty Supply • 9 Council Drive • PO Box 417 • Woodsboro, MD 21798 • [www.sssupply.com](http://www.sssupply.com)