




VAN-MET® MODEL FCI-250
THREE HOUR FIRE-RATED ACCESS DOOR
 Insulated for Wall or Ceiling Application

Offers the largest net size openings available in a three hour fire-rated single leaf panel.




FRONT ELEVATION

STANDARD CONSTRUCTION:

- MATERIAL** - SATIN FINISH GALVANIZED (GALVANNEALED) STEEL.
- PANEL** - 1.31mm [18 ga] , SELF CLOSING.
- LINER** - 0.85mm [22ga].
- FRAME** - 1.61mm [16 ga] UP TO 762mm x 1219mm [30" x 48"]. LARGER SIZES: 1.99mm [14ga].
- FLANGE** - 22mm [$\frac{7}{8}$ "] EXTERIOR FLANGE UP TO AND INCLUDING 914mm x 914mm [36" x 36"]. LARGER SIZES: 32mm [1 $\frac{1}{4}$ ".
- HINGE** - CONTINUOUS ROD HINGE. PIANO HINGE STANDARD ON PANELS EXCEEDING 1219mm [48"] IN A WALL POSITION.
- LATCH** - $\frac{1}{4}$ " ALLEN KEY, WITH INTERIOR RELEASE.
- INSULATION** - 63mm [2 $\frac{1}{2}$ "] HIGH TEMPERATURE
- FINISH** - RUST INHIBITIVE PRIME COAT (OFF-WHITE).

* Specifications subject to change without notice.



SECTION A-A

PROJECT: _____
 CONTRACTOR: _____
 ARCH. OR ENG.: _____
 DATE: _____

These drawings are the property of Maxam Metal Products Ltd, and incorporates information which is proprietary. Publication and/or public distribution in whole or in part is expressly prohibited without the prior written consent of Maxam Metal Products Ltd. The information herein remains the property of Maxam Metal Products Ltd. All rights reserved.

DWN BY KB	DATE Feb. / 2014	DWG. NO. Sheet 1 of 3	REV.
--------------	---------------------	--------------------------	----------



FOR MORE INFORMATION CALL 1-888-926-1365
 Superior Specialty Supply • 9 Council Drive • PO Box 417 • Woodsboro, MD 21798 • www.sssupply.com



VAN-MET® MODEL FCI-250
THREE HOUR FIRE-RATED ACCESS DOOR
 Insulated for Wall or Ceiling Application

STANDARD SIZES

FCI-250, single leaf construction for walls and ceilings.

Rough Opening Size W x H		No. of Latches/ Locks	Weight in kgs.	Weight in lbs.
Metric (mm)	Inches			
305 x 305	12 x 12	1	6.35	14.00
305 x 406	12 x 16	1	7.71	17.00
305 x 457	12 x 18	1	8.16	18.00
305 x 610	12 x 24	1	10.43	23.00
356 x 356	14 x 14	1	7.71	17.00
406 x 406	16 x 16	1	9.07	20.00
406 x 610	16 x 24	1	12.25	27.00
457 x 457	18 x 18	1	10.89	24.00
457 x 610	18 x 24	1	13.15	29.00
457 x 762	18 x 30	1	15.88	35.00
457 x 914	18 x 36	1	19.05	42.00
457 x 1219	18 x 48	1	24.04	53.00
508 x 508	20 x 20	1	12.70	28.00
508 x 610	20 x 24	1	14.52	32.00
508 x 762	20 x 30	1	17.24	38.00
508 x 914	20 x 36	1	20.41	45.00
559 x 559	22 x 22	1	14.52	32.00
559 x 762	22 x 30	1	18.60	41.00
559 x 914	22 x 36	1	21.77	48.00
610 x 610	24 x 24	1	16.33	36.00
610 x 762	24 x 30	1	19.50	43.00
610 x 914	24 x 36	1	23.13	51.00
610 x 1219	24 x 48	2	29.94	66.00
762 x 762	30 x 30	1	23.13	51.00
762 x 914	30 x 36	2	27.67	61.00
762 x 1219	30 x 48	2	35.38	78.00
813 x 813	32 x 32	2	26.31	58.00
914 x 914	36 x 36	2	31.75	70.00

FCI-250, single leaf construction for walls only.

914 x 1219	36 x 48	2	41.28	91.00
914 x 1524	36 x 60	2	51.71	114.00
1016 x 1016	40 x 40	2	38.56	85.00
1016 x 1219	40 x 48	2	44.91	99.00
1016 x 1524	40 x 60	2	56.25	124.00
1219 x 1219	48 x 48	2	52.16	115.00
1219 x 1524	48 x 60	2	65.32	144.00



Net Opening = Width minus 108mm [4¼"]
 Height minus 39mm [1½"]

INSTALLATION:

The frame is manufactured with mounting holes. Factory installed anchor straps are available for masonry, upon request. See installation instructions supplied with panel.

ORDERING:

- WHEN ORDERING, PLEASE SPECIFY WALL OR CEILING APPLICATION.
- PLEASE ORDER BY ROUGH OPENING SIZE.
- WHEN ORDERING THE SECOND DIMENSION GIVEN IS THE HINGE SIDE. (ie. 457mm x 610mm [18" x 24"], THE 610mm [24"] DIMENSION IS THE HINGE SIDE.
- THESE DOORS ARE NON-RETURNABLE.

WARRANTY:

One Year Limited warranty. For complete details see Access Door warranty document.

PROJECT SCHEDULE

- millimeters
- inches

Qty	Rough Opening Size		Wall Application	Ceiling Application
	Width	Height		
			<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>



Model FCI-250 wall and ceiling fire-rated panels are manufactured under the factory inspection service of Intertek (Warnock Hersey) and have a label reading: "Listed access frame and insulated fire door assembly **3 hour fire rating. Vertical and Horizontal Installation** ." Temperature rise maximum 43°C / 77°F at 30 minutes, 149°C / 268°F at 60 minutes.

PROJECT: _____
 CONTRACTOR: _____
 ARCH. OR ENG.: _____
 DATE: _____

PURCHASE ORDER: _____
 APPROVED BY: _____

DWN BY KB	DATE Feb. / 2014	DWG. NO. Sheet 2 of 3	REV.
--------------	---------------------	--------------------------	----------



FOR MORE INFORMATION CALL 1-888-926-1365
 Superior Specialty Supply • 9 Council Drive • PO Box 417 • Woodsboro, MD 21798 • www.sssupply.com



VAN-MET® MODEL FCI-250
THREE HOUR FIRE-RATED ACCESS DOOR
 Insulated for Wall or Ceiling Application

OPTIONS: * - DENOTES ADDITIONAL COST.


MATERIAL :-

- STANDARD MATERIAL - GALVANNEALED STEEL. SEE SHEET 1 OF 3.
- * - OPTIONAL MATERIAL - 304 STAINLESS STEEL WITH A NO. 4 POLISHED FINISH ON THE EXTERIOR SURFACE c/w CONTINUOUS PIANO HINGE.
- * - CONTINUOUS PIANO HINGE.
- * - MASONRY ANCHORS ATTACHED.


HARDWARE :-

- STANDARD HARDWARE - 1/4" ALLEN KEY. SEE SHEET 1 OF 3.
- OPTIONAL HARDWARE - **NOTE: TWO LATCHES ARE REQUIRED ON DOORS LARGER THAN 610mm x 1219mm [24" x 36"]. SEE SHEET 2 OF 3.**

ONE LATCH



TWO LATCHES



CENTER LATCH

TOP LATCH

BOTTOM LATCH

- | | | |
|--------------------------------------------------------------------------------|--------------------------------------------------------------------------------|--------------------------------------------------------------------------------|
| <input type="checkbox"/> - ALLEN KEY | <input type="checkbox"/> - ALLEN KEY | <input type="checkbox"/> - ALLEN KEY |
| <input type="checkbox"/> - RAISED KNURLED KNOB. | <input type="checkbox"/> - RAISED KNURLED KNOB. | <input type="checkbox"/> - RAISED KNURLED KNOB. |
| * <input type="checkbox"/> - NON-LOCKING HANDLE. | * <input type="checkbox"/> - NON-LOCKING HANDLE. | * <input type="checkbox"/> - NON-LOCKING HANDLE. |
| * <input type="checkbox"/> - 1/8" MORTISE PREP ONLY. | * <input type="checkbox"/> - 1/8" MORTISE PREP ONLY. | * <input type="checkbox"/> - 1/8" MORTISE PREP ONLY. |
| * <input type="checkbox"/> - 1/8" MORTISE PREP COMPLETE WITH MORTISE CYLINDER. | * <input type="checkbox"/> - 1/8" MORTISE PREP COMPLETE WITH MORTISE CYLINDER. | * <input type="checkbox"/> - 1/8" MORTISE PREP COMPLETE WITH MORTISE CYLINDER. |

PROJECT: _____

PURCHASE ORDER: _____

CONTRACTOR: _____

APPROVED BY: _____

ARCH. OR ENG.: _____

DATE: _____

DWN BY KB	DATE Feb. / 2014	DWG. NO. Sheet 3 of 3	REV. 0
--------------	---------------------	--------------------------	-----------



FOR MORE INFORMATION CALL 1-888-926-1365
 Superior Specialty Supply • 9 Council Drive • PO Box 417 • Woodsboro, MD 21798 • www.sssupply.com