

SIZING CHART - FHD1.5R

Model FHD1.5R

**One and a Half Hour Fire-Rated Floor Door – Insulated
Wood Framing or Cast in Place Applications**

Inside Dimensions W x L (L = hinge side)		Available with Optional Self Closing mechanism
Hinge side		
Metric (mm) (W x L)	Inches (W x L) ↓	
762 x 610	30 x 24	Yes
914 x 610	36 x 24	Yes
1067 x 610	42 x 24	Yes
1219 x 610	48 x 24	Yes
762 x 762	30 x 30	Yes
762 x 914	30 x 36	Yes
762 x 1219	30 x 48	Yes
762 x 1372	30 x 54	Yes
914 x 762	36 x 30	Yes
914 x 914	36 x 36	Yes
914 x 1219	36 x 48	Yes
914 x 1372	36 x 54	Yes
1067 x 1067	42 x 42	Yes
1219 x 1524	48 x 60	No
1219 x 1219	48 x 48	No
1575 x 1524	62 x 60	No

Sizes shown are for reference. Combinations can be made using the minimum or maximum size in each dimension (W x L) in the size chart as long as the largest dimension of the door is not exceeded in the width or length column. 62" is the maximum width and 60" is the maximum length.

Note: When custom sizing a door, the optional self closing mechanism may not be available.

When ordering, the second dimension given (shown in red) is the hinge side.

Rough in size on standard One and a Half Hour Fire-Rated Doors is plus 146mm (53/4") in both width x length.

Recessed door panels rough in size is plus 152mm (6") in both width x length.

Manufacturing tolerances are +/- 6.35mm (1/4").

Clear opening size in width is approximately minus 159mm (61/4") on smaller doors and varies up to 280mm (11") on the larger doors.

The length dimension (hinge side) has no deduction.



FOR MORE INFORMATION CALL 1-888-926-1365
 Superior Specialty Supply • 9 Council Drive • PO Box 417 • Woodsboro, MD 21798 • www.sssupply.com