

## FIRE EXTINGUISHERS - Multi-Purpose Dry Chemical - Portable Wheeled

ABC dry chemical is a multipurpose extinguishing agent that has uses in offshore rigs, ship docks, remote construction site, storage and loading areas. Not for use on sensitive electronic equipment.



### CLASS A FIRES

Common  
Combustibles



### CLASS B FIRES

Flammable Liquids  
and Gases



### CLASS C FIRES

Energized Electrical  
Equipment

### SPECIFICATIONS:


Portable, large-capacity extinguisher units contain specially-fluidized and siliconized mono ammonium phosphate powder which smothers and breaks the chain reaction on Class B fires, fuses and insulates Class A fires and is a non-conductor of electricity. Non-toxic.

**Conforms to Test Standards:** CAN/ULC-S504 — ANSI/UL299 & CAN/ULC S508 — ANSI/UL711

Designed for one man operation these units are easily transportable through doorways and over rough terrain. Operating Temperature Range: -65°F (-54°C) to 120°F (49°C).

**Construction:** Cylinders are manufactured to DOT specification 4BW240. Highly visible pressure-indicating gauge. Cylinders and carriages are shot blasted, primed and coated with the finest polyurethane powder paint finish that exceeds Underwriter's Laboratories 240 hour salt spray requirements. Hoses are included. All component parts are replaceable. Tow loops are available upon request. Tow loops allow for low speed (15 MPH) towing over gravel or paved surfaces. All units are equipped with all weather semi-pneumatic 12.3 inch diameter, 3.5 inch wide tires.

**Valve Material:** Chrome plated brass

Qty.	Model	Type	Nominal Capacity	Shipping Weight	Overall Height In Inches	Overall Width In Inches	Overall Depth In Inches	Hose Length & Diameter	UL Rating 	Wheel Type	Wheel Dia. In Inches	USCG Approved
	FE50C	ABC Dry Chemical	50 lbs.	154 lbs.	47	24	26.5	25 ft. x .50 in.	10-A:160-B:C	Rubber	12.3 x 3.5	YES
	8FW30110		125 lbs.	300 lbs.	51	26	38	50 ft. x .75 in.	30-A:240-B:C	Rubber	16 x 4	YES
	8FW31120		125 lbs.	387 lbs.	50	24	42	50 ft. x .75 in.	30-A:240-B:C	Rubber	16 x 4	--
	8FW31140		125 lbs.	422 lbs.	55	32	46	50 ft. x .75 in.	30-A:240-B:C	Steel	36 x 2.5	--
	8FW31150		125 lbs.	434 lbs.	55	32	46	50 ft. x .75 in.	30-A:240-B:C	Steel w/Rubber Tread	36 x 2.5	--
	8FW31110		125 lbs.	325 lbs.	50	24	42	50 ft. x .75 in.	30-A:240-B:C	Rubber	16 x 4	--
	8FW32120		300 lbs.	780 lbs.	58	36	48	50 ft. x 1 in.	30-A:320-B:C	Steel	36 x 6	--
	8FW32140		300 lbs.	806 lbs.	58	36	48	50 ft. x 1 in.	30-A:320-B:C	Steel w/Rubber Tread	36 x 6	--
	8FW32110			657 lbs.	58	36	48	50 ft. x 1 in.	30-A:320-B:C	Steel	36 x 6	--
	8FW32130		300 lbs.	683 lbs.	58	36	48	50 ft. x 1 in.	30-A:320-B:C	Steel w/Rubber Tread	36 x 6	--

**Note:** NFPA regulations also require extinguishers to be inspected when initially placed in service and all local fire code and tagging requirements must be adhered to. All fire extinguisher sizes are nominal. Contact Customer Service for more information about ordering tagged extinguishers in your area.



**JL INDUSTRIES**

Distributor:	Project:
Contractor:	Approved By:
Date:	Architect:
Scale: N/A	Pages: 1 of 1
	Item #:

© 2023 Activar Construction Products Group, Inc.

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ACTIVAR CONSTRUCTION PRODUCTS GROUP, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF ACTIVAR CONSTRUCTION PRODUCTS GROUP, INC. IS PROHIBITED.

REV A -APRIL 2023



## FOR MORE INFORMATION CALL 1-888-926-1365

Superior Specialty Supply • 9 Council Drive • PO Box 417 • Woodsboro, MD 21798 • [www.sssupply.com](http://www.sssupply.com)