## SUBMITTAL: CLEAR VU FIRE-FX2™ FIRE-RATED FIRE EXTINGUISHER CABINETS

## PAGE 1 OF 2

Door and Trim Construction: US10 satin bronze, US3 polished brass, clear anodized aluminum, #4 stainless steel or CRS with white powder coat finish. Flush cabinet doors with a 5/8" door stop are attached by a continuous hinge and equipped with zinc-plated handle and roller catch.

Bubble: Acrylic bubble allows 180° extinguisher visibility. 2 1/2" projection for 1500 series, 3 1/2" projection for 2500 series.

Trim Style and Depth: Recessed - 3/8" flat trim, Semi-Recessed - 1 1/4", 1 1/2" Square Edge or 2 1/2", 3", Rolled Edge. All models have 1-3/4" wide trim on frame

Tub: Constructed of cold rolled steel with white powder-coat finish standard. Non-steel surface-mount cabinet tubs constructed of same material as trim. Fire-resistant material is attached to the exterior of the tub.

Fire Rating: Fire-FX2™ cabinets are UL listed and labeled as an approved membrane penetration firestop system for up to 2 hours in accordance with UL 1479 (ASTM-E814) and CAN/ULC-S115, when properly installed in a wall assembly according to installation instructions.

## STEP 1: SELECT MODEL NUMBER, MATERIAL AND QUANTITY ON CHART (refer to chart below)

A. Determine Trim Style according to wall depth.





1517F25FX2

1537G25/fFX2

1	Ctool	Aluminum	Stainless	Bronze	Brass	Trim Chul	1		В	_	-	-	\A/		n	Extinguishers Mounted on the Tub	
		Door Materia	al and Series	s					Tub ID		Fram	e OD	F	X Wall Ope	ening	Accommodates Following	
L	<b>27</b> B	Bronze Acrylic Bul	oble				Custom Stainles	s Finishes #	£ 6, #7, #8	View O	nline			Optional C	olor Door/Ti	rim/Tub View Cabinet Colors Online	
L	26 R	Red Acrylic Bubble	e for 15xx Mod	dels Only			Stainless Steel	Γub #4 Satin	Finish (Sta	ainless M	lodels)			Commande	er Alarm <b>CA</b>	A	
L	<b>25</b> C	Clear Acrylic Bubb	ole			Futura Embosse	d "Fire" Har	ndle in!	Mill \	WhiteI	Red	Dark Bronz	Dark Bronze Anodized Aluminum Finish (pull to match) Pt # changes from "2" to "9				
L		, ,					White Vertical F	E Letters LC	CVWFE					Brass: US4	Satin Bras	ss Finish View Bronze & Brass Finishes Online	
t		ull Acrylic Glazing	0 Coft LokTM	ı			Red Vertical FE	Letters LDC	VRFE					Bronze:	_US9 Brigh	nt Polished, US10B Oil-rubbed Finishes	
Γ	<b>F</b> Fu	ıll Acrylic Glazing					Black Vertical Fl	E Letters LD	CVBFE								
	STEP 2:	SELECT 1 DO	OR STYLE I	- or G & 1 G	LAZING S	YLE	SIEP 3 : OP II	ONAL FEA	ATURES	<u>ai adl</u>	DED COS	I (SELE	CI AN	<u>Y)</u>			

Door Waterial and Series							i ub iD			Fraille OD		rx wall Opening			A commodetes Fellouina					
	Steel		Aluminum		Stainless Steel		Bronze US10		rass JS3	Trim Style	Α	В	С	E	F	W	Н	D	Accommodates Following Extinguishers Mounted on the Tub	
	1515		1525		1535		1545		1555	Flat trim	10 1/2	24	4	13 7/8	27 3/8	12 13/16	26 5/16	4 15/16	On any in 10 On Invest 0 5 40	
	1516		1526		1536		1546		1556	1 1/2" Square	10 1/2	24	4	13 7/8	27 3/8	12 13/16	26 5/16	3 11/16	Cosmic & Galaxy 2.5-10, Mercury 2.5-5, Sentinel 5	
	1517		1527		1537		1547		1557	3" Rolled	10 1/2	24	4	13 7/8	27 3/8	12 13/16	26 5/16	2 3/16	Welculy 2.5-5, Sentine 5	
	2515		2525		2535		2545		2555	Flat trim	14	30	4	17 3/8	33 3/8	16 5/16	32 5/16	4 15/16	Cosmic & Galaxy 2.5-10, Cosmic FE20A,	
Г	2516		2526		2536		2546		2556	1 1/4" Square	14	30	4	17 3/8	33 3/8	16 5/16	32 5/16	3 15/16	Mercury 2.5-15 (FM11A & FM15A), Sentinel 5, Saturn	
	2517		*2527		2537				-	2 1/2" Rolled *	14	30	*4	17 3/8	33 3/8	16 5/16	32 5/16	*2 11/16	15 & 25, Grenadier P, Nebula 270 & 272	

<sup>\*</sup>Add 5/8" to wall depth for a cabinet with an aluminum frame.

It is the responsibility of the customer to communicate specifications and product performance requirements that are needed for their application. This document is intended to convey potential product configurations and offerings. It is not to be used to imply or represent a specification or rating, of finished products shipped. Detailed, specific submittals can be created upon request. It is the responsibility of the customer to specify product accordingly to comply with local laws, codes, and ordinances.

	Distributor:	Quantity:			
JL INDUSTRIES	Contractor:	Approved By:			
	Model #:	Architect:			
	Project:	Date:	© 2023 Activar Construction Products Inc		
	5/25/2023				



Models indicated in **blue** meet ADA 4" projection standards.

## SUBMITTAL: CLEAR VU FIRE-FX FIRE-RATED FIRE EXTINGUISHER CABINETS PAGE 2 OF 2 Fire-Span<sup>™</sup> Insulation ←→ 1" Typical Foil-Backed → | ← 3/16" Typical Typical 3-1/2" Wood Framing Attach to Wall \_\_Tub **Through Holes** or 4" Metal Framing Provided Typical 1-1/4"(3.17cm) 3-1/2" Wood Framing Fully Recessed or 4" Metal Framing or 1-1/2"(3.8cm) 3/8" Flat Trim 3" (7.65cm) or Return Trim 2-1/2" (6.4cm) Rolled Edge Trim Typical 5/8" Gypsum **CABINET DIMENSIONS** 1555F27 FX 2515F25FX 2527G25FX 1536F25FX 1545G26FX



FOR MORE INFORMATION CALL 1-888-926-1365

Superior Specialty Supply ● 9 Council Drive ● PO Box 417 ● Woodsboro, MD 21798 ● www.sssupply.com